PTO/SB/21 (09-06) Approved for use through 03/31/2007. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

der the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.


111					
3)		Application Number	10/758,152		
TRANSMITTAL FORM		Filing Date	January 15, 2004		
		First Named Inventor	Jeremy Wickins		
		Art Unit	1723		
e used for all correspondence after initial	filing)	Examiner Name	Terry K. Cecil		
Number of Pages in This Submission	12	Attorney Docket Number	1003-0059		

Tota	al Number o	f Pages in This Submission	12	Atto	rney Docket Numbe	r 1003-0	059	
ENCLOSURES (Check all that apply)								
		nsmittal Form Fee Attached nent/Reply		Drawing(s) Licensing-related Papers Petition Petition to Convert to a			After Allowance Communication to TC Appeal Communication to Board of Appeals and Interferences Appeal Communication to TC (Appeal Notice, Brief, Reply Brief)	
	After Final Affidavits/declaration(s) Extension of Time Request Express Abandonment Request Information Disclosure Statement	Provisional Application Power of Attorney, Revocation Change of Correspondence Address Terminal Disclaimer Request for Refund CD, Number of CD(s) Landscape Table on CD					Proprietary Information Status Letter Other Enclosure(s) (please Identify below): - Priority Document - Return Receipt Postcard	
	Reply to	Copy of Priority nt(s) Missing Parts/ ete Application Reply to Missing Parts under 37 CFR 1.52 or 1.53	Rema	irks				
		SIGNA	TURE C	FAP	PLICANT, ATT	ORNEY,	OR AG	ENT
Firm N	lame	Cook, Alex, McFarro	n, Manz	o, Cu	ımmings & Mehl	er, Ltd.		
Signat	Signature Earne (Kealing							
Printed name Edward M. Keating						9		
Date		December 4, 2006				Reg. No.	20,64	6
CERTIFICATE OF TRANSMISSION/MAILING								

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

Signature	Susan Shield		
Typed or printed name	Susan Shick	Date	December 4, 2006

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.





IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:

Serial No.:

Jeremy Wickins

10/758,152

l Examiner:

]

Terry K. Cecil

Filed:

January 15, 2004

Art Unit

1723

For:

WASTEWATER TREATMENT

Confirmation No.

4633

APPARATUS

Certificate of Mailing

I hereby certify that this correspondence is being deposited with the United States Postal Service as first-class mail in an envelope addressed to: Commissioner for Patents, Washington, DC on December 4, 2006.

Edward M. Keating Registration No. 20,646

Commissioner for Patents P. O. Box 1450 Alexandria, VA 22313-1450

PRIORITY DOCUMENT

Enclosed is a certified copy of British Patent Application No. 0301092.3, filed on 17 January 2003, which is being filed in support of Applicant's claim for priority under 35 U.S.C. §119(a)(d) or (f).

Respectfully submitted,

Edward M. Keating Registration No. 20,646

COOK, ALEX, McFARRON, MANZO CUMMINGS & MEHLER, LTD. 200 W. Adams St., Suite 2850 Chicago, IL 60606 (312) 236-8500








The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ

f, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as riginally filed in connection with the patent application identified therein.

accordance with the Patents (Companies Re-registration) Rules 1982, if a company named this certificate and any accompanying documents has re-registered under the Companies Act 30 with the same name as that with which it was registered immediately before re-istration save for the substitution as, or inclusion as, the last part of the name of the words blic limited company" or their equivalents in Welsh, references to the name of the company his certificate and any accompanying documents shall be treated as references to the name which it is so re-registered.

cordance with the rules, the words "public limited company" may be replaced by p.l.c., P.L.C. or PLC.

istration under the Companies Act does not constitute a new legal entity but merely to the company to certain additional company law rules.



Signed Flores General

Dated 19 January 2004

CERTIFIED COPY OF PRIORITY DOCUMENT

An Executive Agency of the Department of Trade and Industry

Request for grant of a patent

an explanatory leaflet from the Patent Office to belp

(See the notes on the buck of this form. You can also get

Pat 's Form 1/77

Fatents 45 1977 (Rule 16) Patent Office

17JAN03 E777971-1 D02808 P01/7700 0.00-0301092.3

THE PATENT OFFICE

17 JAN 2003

RECEIVED BY FAX

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

you fill in this form)

DJC/AM-Wickins

Patent application number
 (The Patent Office will fill in this part)

0301092.3

17 JAN 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Jeremy Wickins, Blackstone Cottage, 41 Leylands Road, Burgess Hill, Sussex RH15 BAF

6061493001

4. Title of the invention

Wastewater treatment apparatus

Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Bromhead & Co., 37 Great James Street, London WC1N 3HB

Patents ADP number (if you know it)

455039

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know is) the or each application number

Country F

Priority application number
(If you know it)

Date of filing
(day / month / year)

 If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer Yes' 4):

No

a) any applicant named in part 3 is not an inventor, or

- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate hody. See now (d))

Patents Form 1/77

ents Form 1/77

9. Enter the number of sheets for any of the following items you are filling with this form. Do not count copies of the same document

Continuation sheets of this form

Description

Claim(s)

Abstract

Drawing(s) 2×1

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

> Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature Brownead e Co. Date 17/01/03

12. Name and daytime telephone number of person to contact in the United Kingdom David J. Crouch 0207 405 7010

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to probibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication bas been given, or any such direction has been revoked.

- a) If you need belt to fill in Ints form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

-1-

Wastewater treatment apparatus

invention relates to wastewater present treatment apparatus comprising at least one pre-tank and a reactor tank between which a transfer connection is provided to enable wastewater to be transferred from the or each pre-tank to the reactor tank, and in which the reactor tank is provided with a biomass and aeration equipment to enable the wastewater to be treated in the reactor tank.

It is established practice in the water industry to 10 determine the capacity of the apparatus for dealing with storm conditions in terms of the flow the apparatus has to deal with in dry weather. Thus, to deal with storm conditions, the apparatus is further provided with storm tanks, and overflows or weirs are provided to feed excess 15 flow to these storm tanks. Normally, at least two storm tanks are provided, with the second storm tank beginning to fill after the first has been filled. This increases the likelihood that solids will scutle in these storm tanks. However, in the event that the storm tanks cannot 2.0 storm conditions, ultimately water cope with the overflows from the second storm tank through a screen and Typically, the storm tanks are into a river or stream. required to be capable of containing the amount of 25 wastewater that flows at, say, three times the dry weather flow for a period of at least two hours.

After the storm subsides, the contents of the storm tanks are passed back to the apparatus for treatment,

10

15

20

25

-2-

with scraping equipment in the storm tanks to scrape solids settled off the bottom, also to be returned to the treatment apparatus. This also requires odour control in addition to duty stand-by of all the pumps and equipment.

The provision of storm tanks, scraping equipment and odour control all increase the cost of the apparatus.

The present invention seeks to provide a remedy.

Accordingly, the present invention is directed to wastewater treatment apparatus having the construction the opening paragraph of the present in set specification, characterised in that the capacity of the pre-tank or pre-tanks enables it or them to retain the storm flow for a sufficient period of time and in that the or one of the pre-tanks is provided with a storm overflow, whereby even in storm conditions the reactor tank remains effective and settled solids from the storm flow in the pre-tank or one of the pre-tanks are transferred at intervals to the reactor tank, and in the event of persistence of the storm conditions, excess wastewater is released via the storm overflow without interrupting operation of the reactor tank.

Preferably, the or each pre-tank is provided with a stirrer. This provides the means to maintain a degree of homogeneity of the wastewater in non-storm conditions. Instead of or in addition to the stirrer there may be provided aeration equipment in the or each pre-tank.

At least one of the pre-tanks may be provided with a level sensor to switch-off such a stirrer and/or aeration

10

-3-

equipment once the level of the wastewater in that tank rises above a predetermined level.

This increases the likelihood that solids will settle in the or each pre-tank in storm conditions. The position at which the transfer connection opens into the or each pre-tank may be provided with a cover to reduce the turbulence of fluid within that tank, so that it is not unduly unsettled in storm conditions, when transfer takes place.

The or each cover may comprise a plate.

The storm overflow may comprise a weir as a simple means of dealing with excess wastewater.

There may be two pre-tanks connected together via the transfer connection. Preferably, with two such tanks, they are provided with respective inlets, each 15 with its own shut-off valve, as well as two outlets to the transfer connection also with respective shut-off valves. This enables one tank to be isolated from the rest of the apparatus and serviced whilst the other pretank remains in operation, which in turn enables the 20 apparatus to be serviced without being shut down. In the event of storm conditions, the inlet to one of the pretanks may then be closed so that the flow is directed into only one of the pre-tanks for initial settlement.

Once that tank cannot accommodate further flow, both 25 shut-off valves of the outlets can be opened to enable fluid to flow into the other of the pre-tanks before, ultimately, excess flow flows out through the storm

-4-

overflow.

5

10

20

25

The present invention extends to a method of treating wastewater comprising feeding wastewater to at least one pre-tank from which it is fed at intervals to a reactor tank containing a biomass and aeration equipment to treat the wastewater characterised in that the pre-tank or pre-tanks have a capacity to enable it or them to retain storm flow for a sufficient period of time whilst the reactor tank remains effective and settled solids in one of the pre-tanks are transferred at intervals to the reactor tank and in that in the event of persistence of storm conditions, excess wastewater is released via a storm overflow provided in the or one of the pre-tanks without interrupting operation of the reactor tank.

of wastewater treatment apparatus embodying the present invention will now be described with reference to the accompanying drawing, the only figure of which shows the apparatus in diagrammatic plan form.

The apparatus shown in the only figure of the drawings comprises two pre-tanks 10 and 12 provided with respective inlets 14 and 16 connected to a common feed line 18 via respective shut-off valves 20 and 22. At the base of each pre-tank 10 and 12 there is a sump 24 and 26 respectively leading to respective outlets 28 and 30. The sump and the outlets are covered by respective cover plates 32 and 34 with a relatively small spacing between the plates and the base of the reactor tanks 10 and 12.

10

15

-5-

The outlets 28 and 30 are in turn reconnected to a common transfer line 38 to a reactor tank 40 via respective shut-off valves 42 and 44.

The base of each pre-tank 10 and 12 is provided with an aerator 46 and 48, respectively, and also a mechanical The stirrers are stirrer 50 and 52, respectively. provided with respective motors 49 and 51. Pumps 53 and 55 are also provided for each aerator 46 and 48 to pump air therethrough and pumps 57 and 59 are also provided to pump wastewater from each pre-tank 10 and 12 to the transfer line 38.

Control of the motors and pumps is determined by a microprocessor 61. In addition, the output of a level sensor 62 provided in the pre-tank 10 is connected to that processor.

An overflow weir 64 is provided at a higher level in the pre-tank 10. This discharges wastewater via a discharge line 66 and a screen 68 to a river or stream 70.

- Under normal conditions of flow, for example in dry 20 weather conditions, wastewater is fed by the feed line 18 to the pre-tanks 10 and 12 via the inlets 14 and 16. The wastewater in those pre-tanks is continually moved around by the stirrer 50 and 52 and the aerators 46 and 48.
- Under a pre-selective regime, the microprocessor 61 25 causes the appropriate pump to operate to transfer wastewater from the pre-tanks 10 and 12 to the reactor tank 40.

10

15

20

-6-

In the event that the pre-tanks require servicing and cleaning, one of them is isolated by shutting off its inlet and outlet shut-off valve, whilst the other continues to operate. Normally, however, both shut-off valves 42 and 44 are open so that the wastewater is balanced equally between the two pre-tanks 10 and 12.

During storm conditions, wastewater rises in the pre-tanks 10 and 12 at a rate faster than the transfer of wastewater to the reactor tank 40. Once the level exceeds that determined by the sensor 62, the signal to the microprocessor 61 causes the stirrers 50 and 52 and the aerators 46 and 48 to be stopped so that they no longer stir up solids in the tanks. As a result, as the water level in the pre-tanks rises, sludge and solids more easily settle in these tanks. Sludge is removed from the pre-tanks under the normal treatment regime via the transfer line 38 to the reactor 40. The cover plates 32 and 34 reduce the turbulence caused when sludge is drawn off from the pre-tanks 10 and 12 to the reactor tank 40, reducing the extent to which the sludge and solids which remain in the pre-tanks during storm conditions are disturbed.

In the event that the storm conditions persist, ultimately water flows out of the pre-tank 10 into the river 70 via the line 66 and the screen 68. prevents undesirable solids entering into the river or stream. At the same time, shut-off valves 42 and 44 remain open so that the levels in the pre-tanks 10 and 12

10

-7-

remain substantially equal.

Once the storm conditions have subsided, some of the biomass in the reactor tank 40 may be fed back to the reactor tanks 10 and 12 to assist the apparatus in dealing with the increased load from the storm. However, it will be appreciated that as a result of the construction of the illustrated apparatus, no additional storm tanks are required, and no cleaning or scraping of any such storm tanks is required.

Many modifications and variations to the illustrated apparatus may occur to the reader without taking it outside the scope of the present invention. To give one example only, each pre-tank 10 and 12 could be provided with its respective overflow weir 64.

